

■仕様 (ストレートヒータ及びユニットヒータ)

ストレートヒータ												ユニットヒータ(反射板付)				
型式	電圧 (V)	容量 (W)	ヒータ径 (φd)	A(全長) (mm)	B(発熱長) (mm)	C (mm)	φD (mm)	φE (mm)	φF (mm)	G (mm)	R (mm)	型式	電圧 (V)	容量 (W)	L(反射板長) (mm)	重量 (kg)
RS4- 350E	100	350	14	388	250	34	24	28	23	15	3.5	RU4- 350E	100	350	265	0.5
" - 500E	"	500	"	488	350	"	"	"	"	"	"	" - 500E	"	500	365	0.6
" - 500P	200	500	"	488	350	"	"	"	"	"	"	" - 500P	200	500	365	0.6
" - 750E	100	750	"	638	500	"	"	"	"	"	"	" - 750E	100	750	515	0.8
" - 750P	200	750	"	638	500	"	"	"	"	"	"	" - 750P	200	750	515	0.8
" -1000P	"	1000	"	788	650	"	"	"	"	"	"	" -1000P	"	1000	665	0.9
" -1200P	"	1200	"	938	800	"	"	"	"	"	"	" -1200P	"	1200	815	1.1
" -1500P	"	1500	"	1138	1000	"	"	"	"	"	"	" -1500P	"	1500	1015	1.3
RS7- 750E	100	750	17	538	400	"	26	"	"	"	"	RU7- 750E	100	750	415	0.7
" -1000P	200	1000	"	738	600	"	"	"	"	"	"	" -1000P	200	1000	615	0.9
" -1200P	"	1200	"	788	650	"	"	"	"	"	"	" -1200P	"	1200	665	1.0
" -1500P	"	1500	"	938	800	"	"	"	"	"	"	" -1500P	"	1500	815	1.1
" -1600P	"	1600	"	1038	900	"	"	"	"	"	"	" -1600P	"	1600	915	1.2
" -1800P	"	1800	"	1138	1000	"	"	"	"	"	"	" -1800P	"	1800	1015	1.5
RS0-1000P	"	1000	20	646	500	38	30	33	26	16	4.5	RU0-1000P	"	1000	515	0.8
" -1200P	"	1200	"	746	600	"	"	"	"	"	"	" -1200P	"	1200	615	1.0
" -1500P	"	1500	"	846	700	"	"	"	"	"	"	" -1500P	"	1500	715	1.0
" -1600P	"	1600	"	896	750	"	"	"	"	"	"	" -1600P	"	1600	765	1.1
" -1800P	"	1800	"	1046	900	"	"	"	"	"	"	" -1800P	"	1800	915	1.3
" -2000P	"	2000	"	1146	1000	"	"	"	"	"	"	" -2000P	"	2000	1015	1.5